NSN 5945-01-326-0561

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-326-0561

view Online at https://aerobasegroup.com/nsn/5945-01-526-0561
Overall Length:
1.280 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.490 inches single mounting facility and 0.510 inches single mounting facility
Overall Height:
0.850 inches
Overall Width:
0.810 inches
Mounting Slot Width:
0.123 inches single mounting facility and 0.142 inches single mounting facility
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Surface Treatment:
Tin plated
End Application:
Fuel manageme
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
540.0 ohms single winding and 660.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Cubic Measure:
0.881 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

NSN 5945-01-326-0561

Electromagnetic Relay - Page 2 of 2



Time Delay:

0.006 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.062 inches single mounting facility and 1.078 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

16 wire hook all functions

Specification Data:

81349-mil-r-6106/39 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300