## NSN 5945-01-326-0629

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-326-0629 **Thread Class:** 2b mounting facility hole **Body Style:** O-frame Center To Center Distance Between Mounting Facilities Parallel To Width: 0.937 inches **Body Length:** 1.740 inches **Body Width:** 1.570 inches **Body Height:** 1.680 inches **Actuator Length:** 0.625 inches **Fragility Factor:** Moderately rugged **Actuator Diameter:** 0.438 inches **End Application:** 5895-01-316-2747 central, communications Frequency In Hertz: 60.0 **Inclosure Type:** Fully enclosed **Magnetic Coil Quantity:** 1 **Electrical Resistance:** 42.00 ohms **Duty Type:** Intermittent **Terminal Location:** One side **Voltage Rating In Volts:** 120.0 ac **Mounting Facility Type And Quantity:** 2 threaded hole **Storage Type:** General purpose warehouse **Cubic Measure:** 4.392 cubic inches

Thready Qty Per Inch (tpi): 32 mounting facility hole

## **NSN 5945-01-326-0629** Electrical Solenoid - Page 2 of 2



Actuator Stroke Type:
Pull
Linear Force Delivered:
63.00 ounces
Power Takeoff Connection Type:
Slotted-drilled
Energizing Stroke Maximum Length:
0.375 inches
Power Takeoff Connection Hole Diameter:
Between 0.126 inches and 0.130 inches
Thread Size:
0.190 inches mounting facility hole
Mounting Facility Pattern:
Two position in-line
Thread Series Designator:
Unf mounting facility hole
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A134a0