

View Online at <https://aerobasegroup.com/nsn/5945-01-326-7613>

Overall Length:

1.320 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.810 inches single mounting facility

Overall Height:

Between 1.448 inches and 1.488 inches

Overall Width:

0.410 inches

Environmental Protection:

Hermetic and shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.076 inches single mounting facility and 0.116 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

Test set, mk43

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

450.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.805 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

26.7 milliamperes dc single winding

Time Delay:

0.015 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Energizing Element Power Rating:

80.0 milliwatts

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300