

View Online at <https://aerobasegroup.com/nsn/5945-01-327-0952>

Overall Length:

Between 0.775 inches and 0.799 inches

Overall Height:

Between 0.500 inches and 0.548 inches

Overall Width:

Between 0.378 inches and 0.402 inches

Environmental Protection:

Shock resistant and vibration resistant

Fragility Factor:

Moderately rugged

Contact Material:

Gold and silver

End Application:

5895-01-167-2479 an/fsc-9 (v) , switching syste

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

1.4 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Cubic Measure:

0.160 cubic inches

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.003 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

250.0 ac and 220.0 dc

Precious Material And Location:

Contacts gold and contacts silver

Precious Material:

Gold and silver

Terminal Type And Quantity:

8 pin all functions

Specification Data:

25512-450015 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300