

View Online at <https://aerobasegroup.com/nsn/5945-01-327-4324>

Overall Length:

1.320 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.060 inches single mounting facility and 1.080 inches single mounting facility

Overall Height:

0.410 inches

Overall Width:

0.410 inches

Unthreaded Mounting Hole Diameter:

0.123 inches single mounting facility and 0.133 inches single mounting facility

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold

End Application:

Panel relay

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.0035 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Energizing Element Power Rating:

190.0 milliwatts

Precious Material And Location:

Contact surfaces gold and contacts silver

Precious Material:

Gold and silver

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300