# NSN 5945-01-328-3813

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-328-3813

## **Overall Length:**

0.770 inches

## **Overall Height:**

0.375 inches

# Overall Width:

Between 0.290 inches and 0.310 inches

#### **Fragility Factor:**

Moderately rugged

#### **End Application:**

Dpm 22 7m upg

# Winding Quantity:

1

#### **Purpose For Which Designed:**

General

**Coil Quantity:** 

1

## Winding Dc Resistance Rating:

112.5 ohms single winding

Duty Type:

Continuous

## Mounting Facility Type And Quantity:

1 printed circuit terminal single mounting facility

## Storage Type:

General purpose warehouse

#### **Cubic Measure:**

0.089 cubic inches

## Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

# Operating Voltage Rating And Type At Specificationified Temp:

5.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes dc resistive load

# Main Contact Maximum Voltage Rating In Volts:

100.0 dc

# Test Data Document:

81349-mil-r-83516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

14 pin all functions

# **Specification Data:**

81349-mil-r-83516/1 government specification

# Shelf Life:

N/a

# NSN 5945-01-328-3813

Reed Relay - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300

