NSN 5945-01-329-1145

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-329-1145

Overall Length:

0.575 inches

Overall Height:

0.169 inches

Overall Width:

0.350 inches

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

End Application:

An/tyq-2 (v) 1

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

318.8 ohms single winding and 431.3 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.034 cubic inches

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.006 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Special Features:

Established failure rate 1.0 percent

NSN 5945-01-329-1145

Electromagnetic Relay - Page 2 of 2



Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
10 pin all functions
Specification Data:
81349-mil-r-39016/47 government specification
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No
Fig:
A03300