# NSN 5945-01-329-7858

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-329-7858

| Overall Length:   |
|---|
| 0.405 inches  |
| Overall Height:   |
| 0.300 inches  |
| Overall Width:  |
| 0.370 inches  |
| Environmental Protection:                                     |
| Hermetic  |
| Fragility Factor:   |
| Moderately rugged   |
| End Application:  |
| An/tyq-2 (v) 1  |
| Winding Quantity:   |
| 1   |
| Purpose For Which Designed:                                   |
| General   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:                                 |
| 880.0 ohms single winding                                     |
| Duty Type:  |
| Continuous  |
| Arc Quenching Method:   |
| Air   |
| Mounting Facility Type And Quantity:                          |
| 1 plug-in terminal single mounting facility                   |
| Storage Type:   |
| General purpose warehouse                                     |
| Features Provided:  |
| Coil voltage suppression and polarized                        |
| Cubic Measure:  |
| 0.045 cubic inches  |
| Nonpile-up Main Contact Arrangement:                          |
| 2 pole, double throw, one position momentary                  |
| Criticality Code Justification:                               |
| Feat  |
| Time Delay:   |
| 0.004 seconds fixed release time                              |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 18.0 volts dc 25 degrees celsius single winding               |
| Main Contact Load Current Rating At Maximum Rated Voltage:    |
| 23act 2000 Carrott Rading /tt maximum ration voitage.         |

100.0 milliamperes dc lamp load

## NSN 5945-01-329-7858

Electromagnetic Relay - Page 2 of 2



#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Special Features:** 

Failure rate: 0.1 percent per 10, 000 operations

#### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

8 pin all functions

#### **Specification Data:**

81349-mil-r-39016/19 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A03300