NSN 5945-01-330-3489

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-330-3489

Thread Class:

2a single mounting facility

Overall Length:

Between 1.990 inches and 2.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.615 inches single mounting facility and 0.635 inches single mounting facility

Overall Height:

Between 1.210 inches and 1.250 inches

Overall Width:

Between 0.960 inches and 1.000 inches

Environmental Protection:

Hermetic and dustproof

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.865 inches single mounting facility and 0.885 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

Nrsts

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

Duty Type:

Continuous

Arc Quenching Method:

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

2.411 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

NSN 5945-01-330-3489

Electromagnetic Relay - Page 2 of 2



	Time	Del	lay:
--	------	-----	------

1.00 seconds adjustable operate and release time and 300.00 seconds adjustable operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300