## NSN 5945-01-330-5318

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-330-5318
Overall Length:
Between 0.980 inches and 1.020 inches
Overall Height:
Between 0.409 inches and 0.449 inches
Overall Width:
Between 0.980 inches and 1.020 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Gold and silver and nickel
End Application:
Nrsts
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.44 kilohms single winding and 1.76 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 printed circuit terminal single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Cubic Measure:
0.429 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.01 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-330-5318

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

250.0 ac

**Precious Material And Location:** 

Contacts silver and contacts gold

**Precious Material:** 

Silver and gold

**Terminal Type And Quantity:** 

8 printed circuit all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A03300