

View Online at <https://aerobasegroup.com/nsn/5945-01-331-5858>

Thread Class:

2a second mounting facility

Thread Length:

0.171 inches second mounting facility

Overall Length:

1.165 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.354 inches second mounting facility

Overall Height:

1.187 inches

Overall Width:

0.735 inches

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold

End Application:

De se nav pod

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

7.2 kilohms single winding and 10.8 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 threaded stud second mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.016 cubic inches

Thready Qty Per Inch (tpi):

48 second mounting facility

Thread Size:

0.099 inches second mounting facility

Mounting Facility Pattern:

In-line second mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Gold and silver

Thread Series Designator:

Unc second mounting facility

Terminal Type And Quantity:

16 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300