## NSN 5945-01-332-1039

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-332-1039

view Offiline at https://acrobasegroup.com/hsh/os+o-o1-o52-1009
Overall Length:
4.520 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.500 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.880 inches single mounting facility
Overall Height:
3.090 inches
Overall Width:
3.250 inches
Environmental Protection:
Shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.199 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Othbwcrs
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
6 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
1.00 minutes adjustable operate time and 10.00 minutes adjustable operate time
Operating Voltage Rating And Type At Specificationified Temp:
24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load and 1.0 amperes dc resistive load

## NSN 5945-01-332-1039

Electromagnetic Relay - Page 2 of 2



## **Main Contact Maximum Voltage Rating In Volts:**

480.0 ac and 110.0 dc

**Energizing Element Power Rating:** 

8.0 watts

**Terminal Type And Quantity:** 

8 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300