# NSN 5945-01-332-2617

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-332-2617

## **Overall Length:**

0.810 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility and 1.078 inches single mounting facility

#### **Overall Height:**

0.640 inches

#### **Overall Width:**

0.410 inches

#### **Mounting Slot Width:**

0.133 inches single mounting facility

## **Environmental Protection:**

Dustproof

#### Fragility Factor:

Moderately rugged

## End Application:

F16aircombfit

## Winding Quantity:

1

## **Purpose For Which Designed:**

General

## **Coil Quantity:**

1

## Winding Dc Resistance Rating:

450.0 ohms single winding and 550.0 ohms single winding

#### **Duty Type:**

Continuous

## Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Features Provided:**

Polarized

#### **Cubic Measure:**

0.213 cubic inches

#### **Mounting Facility Pattern:**

In-line single mounting facility

## Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

## Time Delay:

0.006 seconds fixed operate and release time

## Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-332-2617

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

## Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Terminal Type And Quantity:

5 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300