NSN 5945-01-332-4412

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-332-4412

Overall Length:
2.400 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.365 inches single mounting facility and 1.385 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.900 inches single mounting facility
Overall Height:
3.032 inches
Overall Width:
Between 1.990 inches and 2.010 inches
Unthreaded Mounting Hole Diameter:
0.117 inches single mounting facility and 0.179 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Electron sys
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
14.626 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, single throw, normally open, momentary action
Time Delay:
0.025 seconds fixed operate and release time
Nonpile-up Auxiliary Contact Arrangement:
2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action

115.0 ac and 29.0 dc

Auxiliary Contact Maximum Voltage Rating In Volts:

NSN 5945-01-332-4412

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

60.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 threaded stud all functions

Specification Data:

81349-mil-r-6106/10 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300