NSN 5945-01-332-4412

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-332-4412

Overall Length:

2.400 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.365 inches single mounting facility and 1.385 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.900 inches single mounting facility

Overall Height:

3.032 inches

Overall Width:

Between 1.990 inches and 2.010 inches

Unthreaded Mounting Hole Diameter:

0.117 inches single mounting facility and 0.179 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

Electron sys

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

14.626 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

Time Delay:

0.025 seconds fixed operate and release time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

NSN 5945-01-332-4412

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

60.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 threaded stud all functions

Specification Data:

81349-mil-r-6106/10 government specification

Shelf Life: N/a Unit Of Measure: --

Demilitarization:

No

Fiig:

A03300