

View Online at <https://aerobasegroup.com/nsn/5945-01-332-8382>

**Overall Length:**

1.280 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.062 inches single mounting facility and 1.078 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.395 inches single mounting facility and 0.410 inches single mounting facility

**Overall Height:**

0.810 inches

**Overall Width:**

0.640 inches

**Mounting Slot Width:**

0.123 inches single mounting facility and 0.143 inches single mounting facility

**Environmental Protection:**

Hermetic

**Fragility Factor:**

Moderately rugged

**Contact Surface Treatment:**

Tin plated

**End Application:**

Weapons deliv

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

600.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 slotted hole single mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Latching contacts

**Cubic Measure:**

0.663 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Operating Current Rating And Type:**

54.0 milliamperes dc single winding

**Time Delay:**

0.006 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Terminal Type And Quantity:**

16 wire hook all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300