NSN 5945-01-332-9930

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-332-9930

view Offilitie at https://defobasegroup.com/nsi//0340-01-032-9990
Thread Class:
2b single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.850 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.620 inches single mounting facility and 0.630 inches single mounting facility
Overall Height:
1.010 inches
Overall Width:
1.025 inches
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
End Application:
Amraamlau128a
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
290.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 threaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
1.915 cubic inches
Thready Qty Per Inch (tpi):
40 single mounting facility
Thread Size:
0.112 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

NSN 5945-01-332-9930

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.015 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.545 inches single mounting facility and 1.555 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300