

View Online at <https://aerobasegroup.com/nsn/5945-01-332-9930>

**Thread Class:**

2b single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

1.850 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.620 inches single mounting facility and 0.630 inches single mounting facility

**Overall Height:**

1.010 inches

**Overall Width:**

1.025 inches

**Environmental Protection:**

Dustproof

**Fragility Factor:**

Moderately rugged

**End Application:**

Amraamlau128a

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

290.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

3 threaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

1.915 cubic inches

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.112 inches single mounting facility

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Time Delay:**

0.015 seconds fixed operate and release time

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.545 inches single mounting facility and 1.555 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

14 wire hook all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300