# NSN 5945-01-333-0064

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-333-0064
Overall Length:
2.400 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.365 inches single mounting facility and 1.385 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.990 inches single mounting facility and 2.010 inches single mounting facility
Overall Height:
3.032 inches
Overall Width:
2.313 inches
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.148 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
E-3 facs raov
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Latching contacts
Cubic Measure:
16.831 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, single throw, normally open, momentary action

Time Delay:

0.025 seconds fixed operate and release time

## NSN 5945-01-333-0064

Electromagnetic Relay - Page 2 of 2



#### **Nonpile-up Auxiliary Contact Arrangement:**

1 pole, double throw, one position momentary

**Auxiliary Contact Maximum Voltage Rating In Volts:** 

200.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:** 

29.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac lamp load and 20.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:** 

200.0 ac and 28.0 dc

#### **Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

500.0 dual 16 stage ac lamp load and 500.0 dual 16 stage dc lamp load

#### **Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

11 solder stud all functions

#### **Specification Data:**

81349-mil-r-6106/11 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

\_

**Demilitarization:** 

No

Fiig:

A03300