

View Online at <https://aerobasegroup.com/nsn/5945-01-333-0064>

**Overall Length:**

2.400 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.365 inches single mounting facility and 1.385 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.990 inches single mounting facility and 2.010 inches single mounting facility

**Overall Height:**

3.032 inches

**Overall Width:**

2.313 inches

**Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:**

0.148 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**End Application:**

E-3 facs raov

**Winding Quantity:**

2

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Latching contacts

**Cubic Measure:**

16.831 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, momentary action

**Time Delay:**

0.025 seconds fixed operate and release time

**Nonpile-up Auxiliary Contact Arrangement:**

1 pole, double throw, one position momentary

**Auxiliary Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

29.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

20.0 amperes ac lamp load and 20.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

500.0 dual 16 stage ac lamp load and 500.0 dual 16 stage dc lamp load

**Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

11 solder stud all functions

**Specification Data:**

81349-mil-r-6106/11 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300