NSN 5945-01-333-0064

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-333-0064
Overall Length:
2.400 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.365 inches single mounting facility and 1.385 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.990 inches single mounting facility and 2.010 inches single mounting facility
Overall Height:
3.032 inches
Overall Width:
2.313 inches
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.148 inches single mounting facility
Fragility Factor:
Moderately rugged
End Application:
E-3 facs raov
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Latching contacts
Cubic Measure:
16.831 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, single throw, normally open, momentary action

Time Delay:

0.025 seconds fixed operate and release time

NSN 5945-01-333-0064

Electromagnetic Relay - Page 2 of 2



Nonpile-up Auxiliary Contact Arrangement:

1 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

29.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac lamp load and 20.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

500.0 dual 16 stage ac lamp load and 500.0 dual 16 stage dc lamp load

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

11 solder stud all functions

Specification Data:

81349-mil-r-6106/11 government specification

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A03300