## NSN 5945-01-333-0880

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-333-0880

**Overall Length:** 0.280 inches **Overall Diameter:** Between 0.275 inches and 0.335 inches **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged **End Application:** Vendor repair Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 112.5 ohms single winding and 137.5 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 terminal single mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 0.025 cubic inches **Nonpile-up Main Contact Arrangement:** 1 pole, double throw, one position momentary **Criticality Code Justification:** Feat Time Delay: 0.004 seconds fixed release time **Operating Voltage Rating And Type At Specificationified Temp:** 6.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 100.0 milliamperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Special Features:** Established reliabili type 0.100 percent **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5945-01-333-0880

Electromagnetic Relay - Page 2 of 2



Terminal	<b>Type</b>	And	Quantity	y:
----------	-------------	-----	----------	----

5 wire lead all functions

**Specification Data:** 

81349-mil-r-39016/23 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300