NSN 5945-01-333-1234

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-333-1234

Th	rea	d C	lass:

2b single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

Between 6.340 inches and 6.460 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.985 inches single mounting facility and 4.015 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.985 inches single mounting facility and 4.015 inches single mounting facility

Overall Height:

Between 5.000 inches and 5.120 inches

Overall Width:

Between 4.470 inches and 4.590 inches

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

End Application:

Starter motor

Frequency In Hertz:

60.0

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

Duty Type:

Continuous

Arc Quenching Method:

Mounting Facility Type And Quantity:

4 threaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

151.815 cubic inches

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

NSN 5945-01-333-1234

Electromagnetic Relay - Page 2 of 2



Mounting	Facility	Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

8 pole, single throw, normally open, momentary action

Operating Voltage Rating And Type At Specificationified Temp:

440.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

18 tab w/screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300