NSN 5945-01-333-4239

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-333-4239
Overall Length:
0.810 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.500 inches single mounting facility
Overall Height:
0.640 inches
Overall Width:
0.810 inches
Mounting Slot Width:
0.141 inches single mounting facility
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
End Application:
1440-01-087-9844 launching station, g
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
360.0 ohms single winding and 440.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.420 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Time Delay:
0.006 seconds fixed operate and release time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

Operating Voltage Rating And Type At Specificationified Temp:

1.062 inches single mounting facility and 1.078 inches single mounting facility

28.0 volts dc 25 degrees celsius single winding

NSN 5945-01-333-4239

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Terminal Type And Quantity:

16 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300