# NSN 5945-01-333-6138

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-333-6138

### **Overall Length:**

1.300 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.406 inches single mounting facility

#### **Overall Height:**

0.625 inches

#### **Overall Width:**

1.075 inches

#### **Case Material:**

Metal

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.120 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

## End Application:

5865-01-219-2097 jamming system

#### Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

300.0 ohms single winding

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## Mounting Facility Pattern:

In-line single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

## Time Delay:

15.00 seconds fixed operate and release time

## Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

## NSN 5945-01-333-6138

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.5 amperes ac inductive load and 6.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300