NSN 5945-01-337-5508

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-337-5508

Overall Length:
0.810 inches
Overall Height:
0.410 inches
Overall Width:
0.410 inches
Environmental Protection:
Shock resistant and vibration resistant
Fragility Factor:
Moderately rugged
Contact Material:
Gold
End Application:
Mm missile
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
2.64 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.136 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.006 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
36.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc

NSN 5945-01-337-5508

Electromagnetic Relay - Page 2 of 2



Energizing Element Power Rating
1.2 watts
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
8 pin all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A03300