## NSN 5945-01-337-7065



Electromagnetic Relay - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5945-01-337-7065 **Case Material:** Plastic **Environmental Protection:** Dustproof **Fragility Factor:** Moderately rugged **Contact Material:** Silver **End Application:** Switchboard Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 424.8 ohms single winding and 519.2 ohms single winding **Duty Type:** Continuous Storage Type: General purpose warehouse **Nonpile-up Main Contact Arrangement:** 3 pole, double throw, one position momentary Time Delay: 0.015 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: **Precious Material And Location:** Terminals silver **Precious Material:** Silver **Terminal Type And Quantity:** 8 quick disconnect, male all functions Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5945-01-337-7065

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300