NSN 5945-01-338-8392



Electrical Solenoid - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5945-01-338-8392 **Thread Class:** 2b mounting facility hole **Thread Direction:** Right-hand mounting facility hole **Body Style:** O-frame **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.937 inches **Body Length:** 1.740 inches **Body Width:** 1.570 inches **Body Height:** 1.620 inches **Actuator Length:** Between 0.667 inches and 0.707 inches **Fragility Factor:** Moderately rugged **Actuator Diameter:** 0.500 inches **End Application:** An/dsm-127-4 **Inclosure Type:** Fully enclosed

Magnetic Coil Quantity:

Electrical Resistance:

100.00 ohms

Duty Type:

Intermittent

Terminal Location:

One side

Voltage Rating In Volts:

120.0 ac

Mounting Facility Type And Quantity:

4 threaded hole

Current Rating:

165.0 milliamperes

Storage Type:

General purpose warehouse

NSN 5945-01-338-8392 Electrical Solenoid - Page 2 of 2



| Cubic Measure: |
|---|
| 4.425 cubic inches |
| Thready Qty Per Inch (tpi): |
| 32 mounting facility hole |
| Actuator Stroke Type: |
| Pull |
| Linear Force Delivered: |
| 50.00 ounces |
| Power Takeoff Connection Type: |
| Slotted-drilled |
| Power Takeoff Connection Hole Diameter: |
| Between 0.123 inches and 0.133 inches |
| Thread Size: |
| 0.164 inches mounting facility hole |
| Mounting Facility Pattern: |
| Four position rectangular |
| Thread Series Designator: |
| Unc mounting facility hole |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A134a0 |
| |