

View Online at <https://aerobasegroup.com/nsn/5945-01-338-9242>

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.445 inches single mounting facility

Overall Height:

0.525 inches

Overall Width:

1.010 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.155 inches single mounting facility and 0.161 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

4935-01-255-2386 test set, guided

Winding Quantity:

2

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

320.0 ohms all windings

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.910 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Time Delay:

10.00 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 wire hook all functions

Specification Data:

81349-mil-r-6106/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300