## NSN 5945-01-338-9244

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-338-9244

Overall Length:
0.8 millimeters
Overall Height:
0.45 millimeters
Overall Width:
0.41 millimeters
Fragility Factor:
Moderately rugged
Contact Material:
Gold and silver
End Application:
An/tyq-2 (v) 1
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
720.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.01 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
12.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
1.25 amperes ac resistive load and 1.25 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
150.0 ac and 150.0 dc
Energizing Element Power Rating:
200.0 milliwatts
Precious Material And Location:
Contacts gold and contacts silver

## NSN 5945-01-338-9244

Electromagnetic Relay - Page 2 of 2



Preci		

Gold and silver

**Terminal Type And Quantity:** 

10 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300