

View Online at <https://aerobasegroup.com/nsn/5945-01-339-0971>

Overall Length:

0.610 inches

Overall Height:

0.527 inches

Overall Width:

0.310 inches

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

End Application:

Minuteman Is

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

44.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Coil voltage suppression and polarized

Cubic Measure:

0.100 cubic inches

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.006 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

5.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate 0.100 percent per 10, 000 cycles

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Specification Data:

81349-mil-r-39016/38 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300