NSN 5945-01-340-0604

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-340-0604 **Overall Length:** 0.405 inches **Overall Height:** 0.280 inches **Overall Width:** 0.370 inches **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 351.0 ohms single winding and 429.0 ohms single winding **Duty Type:** Continuous **Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse **Features Provided:** Coil voltage suppression **Cubic Measure:** 0.042 cubic inches **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary **Criticality Code Justification:** Feat Time Delay: 0.004 seconds fixed release time Operating Voltage Rating And Type At Specificationified Temp: 12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

NSN 5945-01-340-0604

Electromagnetic Relay - Page 2 of 2



Special Features:

Failure rate 0.1 percent per 10, 000 cycles

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Specification Data:

81349-mil-r-39016/18 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300