NSN 5945-01-340-1957



Electrical Solenoid - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5945-01-340-1957 **Body Style:** Open frame **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.875 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 2.938 inches **Body Length:** 2.375 inches **Body Width:** 3.641 inches **Body Height:** 2.469 inches **Environmental Protection:** Dustproof and shock proof and vibration proof and salt spray resistant and sand proof **Unthreaded Mounting Hole Diameter:** 0.196 inches **Maximum Operating Temp:** 45.0 degrees celsius **Fragility Factor:** Moderately rugged **End Application:** Othbwcrs **Inclosure Type:** Partially enclosed, shell **Magnetic Coil Quantity:** 1 **Duty Type:** Continuous **Terminal Location:** One side **Voltage Rating In Volts: Mounting Facility Type And Quantity:** 4 unthreaded hole **Current Rating:** 6.7 amperes **Storage Type:** General purpose warehouse

Cubic Measure:
21.350 cubic inches
Actuator Stroke Type:
Pull

NSN 5945-01-340-1957

Electrical Solenoid - Page 2 of 2



Power Takeoff Connection Type:
U-shaped bracket
Energizing Stroke Maximum Length:
1.000 inches
Power Takeoff Connection Hole Diameter:
Between 0.376 inches and 0.378 inches
Mounting Facility Pattern:
Four position rectangular
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A134a0