# NSN 5945-01-340-1957

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-340-1957

## Body Style:

Open frame

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.875 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.938 inches

#### Body Length:

2.375 inches

#### **Body Width:**

3.641 inches

#### **Body Height:**

2.469 inches

#### **Environmental Protection:**

Dustproof and shock proof and vibration proof and salt spray resistant and sand proof

#### **Unthreaded Mounting Hole Diameter:**

0.196 inches

#### Maximum Operating Temp:

45.0 degrees celsius

### Fragility Factor:

Moderately rugged

#### **End Application:**

Othbwcrs

#### Inclosure Type:

Partially enclosed, shell

#### Magnetic Coil Quantity:

1

## Duty Type:

Continuous

#### **Terminal Location:**

One side

#### Voltage Rating In Volts:

120.0 ac

## Mounting Facility Type And Quantity:

4 unthreaded hole

## **Current Rating:**

6.7 amperes

## Storage Type:

General purpose warehouse

## Cubic Measure:

21.350 cubic inches

## Actuator Stroke Type:

Pull

## NSN 5945-01-340-1957

Electrical Solenoid - Page 2 of 2



Power Takeoff Connection Type: U-shaped bracket Energizing Stroke Maximum Length: 1.000 inches **Power Takeoff Connection Hole Diameter:** Between 0.376 inches and 0.378 inches Mounting Facility Pattern: Four position rectangular Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A134a0