## NSN 5945-01-340-7435

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-340-7435 **Overall Length:** 0.760 inches **Overall Height:** 0.300 inches **Overall Width:** 0.220 inches **Case Material:** Plastic **Environmental Protection:** Dustproof **Fragility Factor:** Moderately rugged **End Application:** llos angeles class ssn (688); tarawa class lha; nimitz class cvn; spruance class dd (963); forrestal class cv; ticonderoga class cg (47); arleight burke class ddg; oliver perry class ffg; wasp class lhd Winding Quantity: 1 **Purpose For Which Designed:** General **Coil Quantity:** 1 Winding Dc Resistance Rating: 500.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 0.050 cubic inches **Criticality Code Justification:** Feat Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

100.0 dc

**Special Features:** 

Weapon system essential

**Terminal Type And Quantity:** 

4 tab, solder lug all functions

## NSN 5945-01-340-7435

Reed Relay - Page 2 of 2



Spec	cific	ation	Data:
------	-------	-------	-------

28480-0490-1608 manufacturers specification control

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300