NSN 5945-01-340-9892

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-340-9892

Overall Length:
0.370 inches
Overall Height:
0.375 inches
Overall Width:
0.335 inches
Environmental Protection:
Salt spray resistant and vibration proof and shock proof

Fragility Factor:

Moderately rugged

End Application:

F15e cbil

Winding Quantity:

1

Purpose For Which Designed:

. .

General

Coil Quantity:

1

Winding Dc Resistance Rating:

3.2 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.046 cubic inches

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.0075 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

NSN 5945-01-340-9892

Electromagnetic Relay - Page 2 of 2



Special Features:

Failure rate level of 0.100 percent per 10, 000 cycles

Terminal Type And Quantity:

9 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300