## NSN 5945-01-340-9892

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-340-9892

Overall Length:
0.370 inches
Overall Height:
0.375 inches
Overall Width:
0.335 inches
Environmental Protection:
Salt spray resistant and vibration proof and shock proof
Fragility Factor:
Moderately rugged
End Application:
F15e cbil
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
3.2 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.046 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.0075 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc

## NSN 5945-01-340-9892

Electromagnetic Relay - Page 2 of 2



Failure rate level of 0.100 percent per 10, 000 cycles

**Terminal Type And Quantity:** 

9 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300