# NSN 5945-01-341-5650

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-341-5650

# Thread Class:

2a single mounting facility

#### **Thread Direction:**

Right-hand single mounting facility

## **Overall Length:**

Between 2.730 inches and 2.770 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.740 inches single mounting facility and 1.760 inches single mounting facility

#### **Overall Height:**

Between 2.120 inches and 2.160 inches

#### **Overall Width:**

Between 2.250 inches and 2.290 inches

#### **Environmental Protection:**

Hermetic

### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.615 inches single mounting facility and 1.635 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

## **End Application:**

Snglanddualpy

#### Frequency In Hertz:

400.0

#### Winding Quantity:

1

# Purpose For Which Designed:

General

# **Coil Quantity:**

1

# Duty Type:

Continuous

#### Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

#### Storage Type:

General purpose warehouse

#### Cubic Measure:

13.358 cubic inches

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Mounting Facility Pattern:

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

# NSN 5945-01-341-5650

Electromagnetic Relay - Page 2 of 2



### Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

28.0 dc

#### **Thread Series Designator:**

Unc single mounting facility

#### **Terminal Type And Quantity:**

14 wire hook all functions

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A03300