NSN 5945-01-341-5650

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-341-5650

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

Between 2.730 inches and 2.770 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.740 inches single mounting facility and 1.760 inches single mounting facility

Overall Height:

Between 2.120 inches and 2.160 inches

Overall Width:

Between 2.250 inches and 2.290 inches

Environmental Protection:

Hermetic

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.615 inches single mounting facility and 1.635 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

Snglanddualpy

Frequency In Hertz:

400.0

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

•

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

13.358 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

NSN 5945-01-341-5650

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300