NSN 5945-01-342-6654

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-342-6654

, , , , , , , , , , , , , , , , , , ,
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Thread Length:
0.310 inches single mounting facility
Overall Length:
1.843 inches
Overall Height:
1.687 inches
Overall Width:
1.510 inches
Fragility Factor:
Moderately rugged
Contact Material:
Silver
End Application:
Bmews site ii
Frequency In Hertz:
Between 50.0 and 60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
7.7 kilohms single winding and 10.5 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
4.695 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:

TITI Caa OIZC

0.138 inches single mounting facility

NSN 5945-01-342-6654

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Time Delay:

0.015 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

230.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac

Energizing Element Power Rating:

2.0 watts

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

5 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300