NSN 5945-01-343-0357



| Electromagnetic relay 1 age 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5945-01-343-0357 |
| Overall Length: |
| 4.520 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.500 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.880 inches single mounting facility |
| Overall Height: |
| 2.830 inches |
| Overall Width: |
| 3.250 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.199 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 6 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |

Cubic Measure:

41.572 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.05 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac and 30.0 dc

NSN 5945-01-343-0357

Electromagnetic Relay - Page 2 of 2



Unit Of Measure:
-Demilitarization:

No

Fiig:

A03300