

View Online at <https://aerobasegroup.com/nsn/5945-01-343-3209>

Overall Length:

3.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches first mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches second mounting facility

Overall Height:

7.000 inches

Overall Width:

2.375 inches

Mounting Slot Width:

0.190 inches first mounting facility

Case Material:

Plastic

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.190 inches second mounting facility

Fragility Factor:

Moderately rugged

End Application:

Transfer pane

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole second mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

65.469 cubic inches

Mounting Facility Pattern:

In-line second mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, single throw, normally open, double make, momentary action and 6 pole, single throw, normally closed, double break, momentary action

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

600.0 ac

Energizing Element Power Rating:

155.0 volts-amperes

Terminal Type And Quantity:

26 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300