## NSN 5945-01-343-8835

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-343-8835

Overall Length:
1.718 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.396 inches second mounting facility and 1.446 inches second mounting facility
Overall Height:
1.310 inches
Overall Width:
0.525 inches
Mounting Slot Width:
0.150 inches second mounting facility
Environmental Protection:
Shock resistant and vibration resistant
Fragility Factor:
Moderately rugged
End Application:
Fuel htr cont
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole second mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Cubic Measure:
1.182 cubic inches
Mounting Facility Pattern:
In-line second mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
-

0.01 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-343-8835

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:** 

120.0 ac and 28.0 dc

**Precious Material And Location:** 

Terminal surfaces gold

Precious Material:

Gold

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300