NSN 5945-01-344-2504

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-344-2504

Overall Length:			
1.718 inches			
Center To Center Distance Between Mounting Facilities Parallel To Length:			
1.396 inches single mounting facility and 1.446 inches single mounting facility			
Overall Height:			
0.525 inches			
Overall Width:			
1.125 inches			
Mounting Slot Width:			
0.150 inches single mounting facility			
Environmental Protection:			
Hermetic			
Fragility Factor:			
Moderately rugged			
Contact Material:			
Silver			
Contact Surface Treatment:			
Gold			
Frequency In Hertz:			
Between 50.0 and 400.0			
Winding Quantity:			
1			
Purpose For Which Designed:			
General			
Coil Quantity:			
1			
Duty Type:			
Continuous			
Arc Quenching Method:			
Air			
Mounting Facility Type And Quantity:			
2 slotted hole single mounting facility			
Storage Type:			
General purpose warehouse			
Cubic Measure:			
1.051 cubic inches			
Mounting Facility Pattern:			
In-line single mounting facility			
Nonpile-up Main Contact Arrangement:			

2 pole, double throw, one position momentary Operating Current Rating And Type:

30.0 milliamperes ac single winding

NSN 5945-01-344-2504

Electromagnetic Relay - Page 2 of 2



Tima	\mathbf{D}^{\sim}	~
Time	Del	ιαν.

0.05 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Terminals silver and surface gold

Precious Material:

Gold and silver

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300