## NSN 5945-01-346-2328

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-346-2328 **Case Material:** Plastic **Environmental Protection:** Dustproof **Fragility Factor:** Moderately rugged **Contact Material:** Silver Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 424.8 ohms single winding and 519.2 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 plug-in terminal single mounting facility **Storage Type:** General purpose warehouse **Nonpile-up Main Contact Arrangement:** 3 pole, double throw, one position momentary Time Delay: 0.015 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load and 5.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 240.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Terminal Type And Quantity:** 11 quick disconnect, male all functions

Shelf Life: N/a **Unit Of Measure:** 

## NSN 5945-01-346-2328

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300