## NSN 5945-01-347-0514

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-347-0514

Overall Length:
0.375 inches
Overall Diameter:
0.370 inches
Environmental Protection:
Hermetic and salt spray resistant and shock resistant and vibration resistant
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:

2.3 kilohms single winding

**Duty Type:**Continuous

Arc Quenching Method:

Winding Dc Resistance Rating:

AIO QUI

Air

**Mounting Facility Type And Quantity:** 

1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

**Cubic Measure:** 

0.040 cubic inches

**Nonpile-up Main Contact Arrangement:** 

1 pole, double throw, one position momentary

**Criticality Code Justification:** 

Feat

Time Delay:

0.004 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

18.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

115.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Special Features:** 

Failure rate level of 1.000 percent per ten thousand cycles

## **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5945-01-347-0514

Electromagnetic Relay - Page 2 of 2



Terminal	Type And	Quantity
5 pin all fu	unctions	

Specification Data:

81349-mil-r-39016/10 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300