

View Online at <https://aerobasegroup.com/nsn/5945-01-347-1824>

Overall Length:

2.187 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches second mounting facility

Overall Height:

2.156 inches

Overall Width:

1.531 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.142 inches second mounting facility and 0.152 inches second mounting facility

Fragility Factor:

Moderately rugged

End Application:

Asge426 ser s

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 unthreaded hole second mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Coil voltage suppression

Mounting Facility Pattern:

Triangle second mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.02 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.844 inches second mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300