## NSN 5945-01-347-1825

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-347-1825

Overall Length:
2.187 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches second mounting facility
Overall Height:
2.156 inches
Overall Width:
1.531 inches
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.142 inches second mounting facility and 0.152 inches second mounting facility
Contact Surface Treatment:
Gold
End Application:
Asge426 ser s
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 unthreaded hole second mounting facility
Features Provided:
Coil voltage suppression
Mounting Facility Pattern:
Triangle second mounting facility
Nonpile-up Main Contact Arrangement:
6 pole, double throw, one position momentary
Time Delay:
0.05 seconds fixed release time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.844 inches second mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
1.5 amperes ac motor load and 1.5 amperes dc motor load
Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## NSN 5945-01-347-1825

Electromagnetic Relay - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
20 pin all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A03300