## NSN 5945-01-347-6413

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-347-6413

Overall Length:
0.370 inches
Overall Height:
0.270 inches
Overall Width:
0.370 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Platinum
Contact Surface Treatment:
Gold
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
45.0 ohms single winding and 55.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
10 terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.283 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.002 seconds fixed operate time0.0015 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
5.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:

200.0 milliamperes ac resistive load and 1.0 amperes dc resistive load200.0 milliamperes dc inductive load100.0 milliamperes dc lamp load

## NSN 5945-01-347-6413

Electromagnetic Relay - Page 2 of 2



## **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Energizing Element Power Rating:** 

450.0 milliwatts

**Precious Material And Location:** 

Contacts palladium and contact surfaces gold

**Precious Material:** 

Gold and palladium

**Terminal Type And Quantity:** 

10 wire lead all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A03300