

View Online at <https://aerobasegroup.com/nsn/5945-01-347-8789>

**Overall Length:**

0.370 inches

**Overall Height:**

0.280 inches

**Overall Width:**

0.370 inches

**Environmental Protection:**

Hermetic and salt spray resistant and shock resistant and vibration resistant

**Fragility Factor:**

Moderately rugged

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

1.56 kilohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

1 plug-in terminal single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

0.038 cubic inches

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Current Rating And Type:**

18.5 milliamperes dc single winding

**Criticality Code Justification:**

Feat

**Time Delay:**

0.004 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

100.0 milliamperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Special Features:**

Failure rate level of 1.000 percent per ten thousand cycles

**Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 pin all functions

**Specification Data:**

81349-mil-r-39016/19 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300